



Hiboost Wide Band Booster Triple Band F13-EDW

900/1800/ 2100MHz **Description**

F13-EDW Wide Band Booster is designed to improve mobile signals for end users directly. It covers any indoor area up to 500 square meters and is guaranteed to supply great communication experience with clearer calls and higher data download speed than ever.




Key Features

- Support 900,1800 and 2100MHz
- Real-time LED display
- Manual and automatic gain control functions
- Self-oscillation protection
- High integration
- Compact and light
- Good heat dissipation for long time operation
- Wide power supply range and low power consumption



Installation Example



1. Outdoor Antenna 2.Booster 3.Indoor Panel Antenna 4.Power Supply

Address: Benno-Strauß-Straße 790763 Fürth Phone: (44)20 3239 5808 E-mail : sales@huaptec.eu
Web site : www.huaptec.eu



Specification

RF Parameter		Uplink	Downlink
Frequency Range	900MHz	880~915MHz	925~960MHz
	1800MHz	1710~1785MHz	1805~1880MHz
	2100MHz	1920~1980MHz	2110~2170MHz
Max .Gain		60dB	65dB
Max .Output Power		17dBm	13dBm
MGC (Step Attenuation)		≥31dB / 1dB step	
Intelligent AGC*	ALC	≥42dB	
	ISO	≥42dB	
Gain Flatness		Typical≤5dB (p-p)	
Noise Figure @ Max. System Gain		Typical≤5dB	
V.S.W.R		Typical≤2	
Group Delay		≤1μs	
Frequency Stability		≤0.01ppm	
Electrical Parameter			
Power Supply		Input AC100~240V,50/60Hz, Output DC12V/7A	
Max. Power Consumption		≤32W	
Input & Output Impedance		50 ohm	
Indicator			
ISO LED	1)	Green: No loop back or no self-oscillation	
	2)	Slow Flashing Green: Slight loop back or self-oscillation	
	3)	Quick Flashing Green: Deep loop back or self-oscillation	
	4)	Quick Flashing Red: Severe loop back or self-oscillation	
	5)	OFF: The booster auto shuts off for protection due to very severe self oscillation.	
Alarm LED	1)	Green: Output power is not full	
	2)	Slow Flashing Green: Full output power	
	3)	Quick Flashing Green: Output power is over rated	
	4)	Quick Flashing Red: The booster auto shuts off for protection due to much over rated output power.	
Mechanical Parameter			
I/O Port Type		N-Female	
Dimension		11*11*2.1inch/280*280*53mm	
Weight		≤11lbs/5KG	
Environment Parameter			
Operating Temperature		-10°C~+55°C	
Environment Conditions		IP40	

* MGC, ALC and ISO share intelligent AGC 42 dB range.

ALC: 42dB automatic gain adjustment range to stabilize the output power.

ISO: 42dB intelligent isolation processing to avoid self-oscillation.

The information in this specification reserves the right to change without notice.