



Huaptec 5D-FB

Overview

5D-FB Coaxial cable is used to transmit radio frequency (RF) signal. Its working frequency range: 0—3GHz



Key Features

- Low loss
- Low VSWR
- Low transmission delay
- Minimum attenuation



Specification

Structural Parameters

Project	material	Diameter(mm)
Inner conductor	Solid Copper or Copper Clad Aluminum	1.80
Dielectric	Physical Foam Polyethylene	5.00
First shield	Bonded Aluminum/Polyester/ Aluminum tape	5.20
Outer conductor	Tinned Copper Braid	5.70
Jacket	Black PVC or Polyethylene	7.50

Electrical Parameters

Mechanical Parameter

Capacitance(Pf/M)	82
Impedance (ohm)	50
Velocity(%)	82
Inner Conductor DC Resistance (Ω /KM)	6.8/10.5
Outer Conductor DC Resistance (Ω /KM)	14.1
Shielded attenuation (dB)	>80

Mechanical and environment Parameters

Storage temperature($^{\circ}$ C)	-25 to +70
Installation temperature($^{\circ}$ C)	-25 to +70
Working temperature($^{\circ}$ C)	- 25 to +70
Minimum bend radius(mm)	27

VSWR

5-3000MHz	\leq 1.20
-----------	-------------

Attenuation(20 $^{\circ}$ C)

Frequency(MHz)	Attenuation(dB/100m)
150	7.80
280	10.80
350	12.10
400	13.00
900	20.20
1200	23.70
1500	26.80
1800	29.70
2200	33.30
2500	35.80